

DOOR OPENER BRINK

For doors up to 250 kg

10DOORBRINK

Single leaf swing door opener, powered opening, powered closing, wind stop. Max. leaf 130 kg and 1000 mm.

10DOORBRINK-S

Single leaf swing door opener, powered opening, spring closing, wind stop. Max. leaf 130 kg and 1000 mm.

10DOORBRINK-SL

Single leaf swing door opener, powered opening, spring closing, wind stop. Max. leaf 100 kg and 1000 mm.

Features:

- commercial use
- max. opening 95°
- for door panels up to 130 kg and 1000 mm
- built-in electronic control unit
- in or out swing
- single or double swing leaf installation

Pros:

- intensive use
- ideal for offices, supermarkets, hospitals and public entrances
- can automate most swing doors, new or existing
- quick and easy installation
- react immediately to any obstacle
- wind stop: resists wind pressure
- high reliability and smooth operation



Technical features

	BRINK / BRINK-S	BRINK-SL
Power supply	115/230 V AC (50 - 60 Hz)	115/230 V AC (50 - 60 Hz)
Motor power supply	24 V DC with encoder	24 V DC with encoder
Absorbed power	120 W	120 W
Opening speed	4 - 12 sec.	4 - 12 sec.
Closing speed	5 - 15 sec.	5 - 15 sec.
Duty cycle	100 %	100 %
Operating temperature	-20° C ÷ +50° C	-20° C ÷ +50° C
Degree of protection	IP 32	IP 32
Max. opening	95°	95°
Max. gate leaf weight	130 kg	100 kg



Compact and reliable operator




The above represented installation does not include safety devices such as safety edges. Their addition depends upon the risk assessment made on any installation in accordance with EN 12445-12453 standards.

Accessories




S-10DOORBST
Track (PULL operation)



Length of door (mm)	Max weight (Kg)
700	130
750	124
800	118
850	113
900	108
950	104
1000	100




S-10DOORBSS
Scissor arm (PUSH operation)



Length of door (mm)	Max weight (Kg)
800	92
850	89
900	85
950	83
1000	80



S-10DOORSS340
Safety sensor for obstacle detection



S-10DOORRAD2
Radar for activation and safety



S-10DOORPROGT
Programming keypad

NEW



S-10DOORRAD
Active infrared motion detector



S-10DOORSELF
Mechanical program switch for BRINK



S-10DOORADM
Microwave radar detector, unidirectional, scanned area 4 m, turtle mode for enhanced pedestrian safety

NEW



S-10DOORSELFBC
Mechanical key switch for BRINK



S-10DOORTL
Microwave, hygienic, touchless, automatic door activation switch, scanned area 4 m, 3 different faceplate included

NEW



S-10DOORKIT2BRK
Aluminium cover for two BRINK openers, complete with cable for Master/Slave connection

